



Proclaim:

PONEY reserves the right of final interpretation for the information contained herein. PONEY corporation does not accept any responsibility for any typing, omissions, inaccuracies, or printing errors in this catalog. We also reserve the right to make possible alternations or modifications which we believe necessary at any time, without notice or interfering with the basic functions of the apparatus.



ZHEJIANG PONEY ELECTRIC CO.,LTD.

Add: 317500, Shiqiaotou Town, Wenling City,

Zhejiang Province, China

Tel: +86 0576 81628288

Fax: +86 0576 81628338

Mail: admin@chinaponey.com

sales@chinaponey.com

www.chinaponey.com



WELDING MACHINE

ZHEJIANG PONEY ELECTRIC
CO.,LTD.

CATALOG





ABOUT US

ESTABLISHMENT : 2009

LOCATION : WENLING.CHINA

FACTORY SQUARE : 8000m²

PRODUCTS : Welding Machine,Cutting Machine ,
Car Battery Charger

HONORS : “TAIZHOU BRRAND PRODUCT”,
“NATIONAL HIGH-TECH INTERPRISE”

CERTIFICATE : CE,RoHS,ETL,GS,ERD,BSCI,
ISO 9001, ISO14001:2015

CERTIFICATE



PONEY enterprise is able to assure its clients the very best in terms of quality, reliability and safety, The sound management and expertise of technology secured the possession of all the most important product certifications BSCI, ISO, CE, GS, ETL, CCC , ROHS, and others.





PROFILE

PONEY limited has positioned itself as a leading manufacturer engaging in the production of welding machine, air plasma cutting machine and car battery charger. A large selection of products in ground-breaking technology , unique and modern designs make our company a competent partner for industry and trade. We have the expertise to provide efficient and effective solutions for our valuable clients and help creating value. PONEY is highly flexible to offer tailored OEM services.

Since establishment in 2009, PONEY has developed a highly matured system for manufacturing , R&D , after sale services and logistics . Continuous innovations, state-of-the-art facilities which guarantee superior quality ,reliability and safety .Maintain ingenuity in each and every detail of products.



painting workshop



modern testing equipment



wave-soldering



housing cover fabrication



PCB processing



advanced SMD machinery

Index



GMAW(MIG/MAG)WELDING MACHINE

MAGICMIG-350DP/500DP	02
MIG-200DP/250DP	03
MIG-200N/250N/350NF	04
MIG-200DP-X/200-X	05
MIG-160-AM/180-AM/-200-AM	06
MIG-180PRO/-200PRO	07
MIG-140T/-160T/-180T/-200T	08
MIG-140SNY/160SNY/180SNY/200SNY	09
MIG-164CT	10
MIG-140E/160E/160N1/-180N1/-200N1	11
mini MIG-140SNY	12
FCW-120RD	13
FCW-120	14



SMAW(MMA)WELDING MACHINE

iARC-140SKN/-160SKN/-180SKN/-200SKN	15
iARC-140/-160/-180/-200	16
iARC-140IL/-160IL/-180IL/-200IL/-225IL	17
MMA-120ZX/140ZX/-140ZX-D	18
MMA-160E/180E/-200E	19
MMA-250/-315/-400/-500	20



GTAW(TIG)WELDING MACHINE

TIG-200I	21
TIG-200i-PRO	22
TIG-250P/280P	23
TIG-160	24



AIR PLASMA CUTTING WELDING MACHINE

CUT-40/-60	25
CUT-80/-100/-120	26



CAR BATTERY CHARGER

CB-10/15/20/30/50 / CD-30R/50R	27
CD-300/400/500/600/800/1000	28

MIG(GMAW) SYNERGIC PROCESSING DIGITAL SIGNAL CONTROL



MIG

High Speed

↑ Increase Efficiency
By 30-50%

MAGICMIG-350DP MAGICMIG-500DP

- Advanced digital signal control SYNERGIC processing.
- Double pulse / Single pulse.
- Separate wire feeder .
- Water cooling .
- Multi-process :MIG , MAG ,FLUX ,MIG synergy , MIG single pulse , MIG double pulse , High speed MIG single pulse , High speed MIG double pulse , TIG LIFT, spot welding . MMA .
- Applicable for materials :iron , cast iron , carbon steel , Er316, Er308 , aluminum 100% ,AlMg5, AISi5, CuSi3, etc .
- Save/load up to 20 jobs .
- Remote loading on welding torch for 5 jobs .
- Welding thickness selectable .
- Versatile functions :Hot start , arc force , anti-stick , burn back , inductance , VRD , 2T,4T, short circuit protection , thermal protection .
- High efficiency and precise welding for demanding and quality welding job.
- Moving wheels and trolley.



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40°C(%)
MAGICMIG-350DP	380V ± 15% 50/60Hz	14	70	30-350	0.8-1.6	1.6-5.0	60
MAGICMIG-500DP	380V ± 15% 50/60Hz	25	70	30-500	0.8-1.6	1.6-6.0	60


MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL



MIG-200DP
MIG-250DP

VOLTAGE
OPTION 110 /220V


- Advanced digital signal control SYNERGIC processing. Save 35 Jobs.
- Double pulse / Single pulse.
- Multi-process :MIG , MAG ,FLUX , MIG synergy , MIG single pulse , MIG double pulse , TIG LIFT , spot welding . MMA .
- Applicable for materials :iron , cast iron , carbon steel , Er316, Er308 , aluminum 100% ,AlMg5, AISi5, CuSi3, etc .
- Versatile functions :Hot start , arc force , anti-stick , burn back , inductance , VRD , 2T,4T, short circuit protection , thermal protection .
- High efficiency and precise welding for demanding and quality welding job.
- Moving wheels and trolley .



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40 °C(%)
MIG-200DP	220V ±15% 50/60Hz	7.0	70	30-200	0.8-1.2	1.6-4.0	40
MIG-250DP	220V ±15% 50/60Hz	9.5	70	30-250	0.8-1.2	1.6-5.0	40
MIG-250DP	220/380V ±15% 50/60Hz	9.5	70	30-250	0.8-1.2	1.6-5.0	40
MIG-250DP	380V ±15% 50/60Hz	9.5	70	30-250	0.8-1.2	1.6-5.0	40

MIG(GMAW)
ANALOGY INVERTER



MIG-200N
MIG-250N
MIG-350NF

- Inverter technology .
- Multi-process MIG, MAG , FLUX, MMA.
- Versatile functions :Hot start , arc force , anti-stick , inductance , thermal protection .
- Professional welding for carbon steel , iron , cast iron , stainless steel.
- Moving wheels and trolley .



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40 °C(%)
MIG-200N	220V ±15% 50/60Hz	7.0	56	30-200	0.8-1.0	1.6-4.0	40
MIG-250N	220V ±15% 50/60Hz	9.5	68	30-250	0.8-1.0	1.6-5.0	40
MIG-350NF	380V ±15% 50/60Hz	9.5	68	30-350	0.8-1.0	1.6-5.0	40


MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL



MIG-200DP-X
MIG-200-X

VOLTAGE
OPTION 110 /220V

- Advanced digital signal control SYNERGIC processing. Save 35 Jobs.
- Double pulse / Single pulse.
- Multi-process :MIG , MAG ,FLUX , MIG synergy , MIG single pulse , MIG double pulse , TIG LIFT , spot welding . MMA .
- Applicable for materials :iron , cast iron, carbon steel , Er316, Er308 , aluminum 100% ,AlMg5, AISi5, CuSi3, etc .
- Versatile functions :Hot start , arc force , anti-stick , burn back , inductance , VRD , 2T,4T, short circuit protection , thermal protection .
- High efficiency and precise welding for demanding and quality welding job.



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40°C (%)
MIG-200DP-X	220V ±15% 50/60Hz	7.0	70	30-200	0.8-1.2	1.6-4.0	60
MIG-200-X	220V ±15% 50/60Hz	7.0	70	30-200	0.8-1.2	1.6-4.0	60


MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL



MIG-160-AM
MIG-180-AM
MIG-200-AM

VOLTAGE
OPTION 110 /220V

- Advanced digital signal control SYNERGIC processing.
- Single pulse.
- Multi-process :MIG , MAG ,FLUX , TIG LIFT , MMA .
- Applicable for materials :iron , carbon steel ,cast iron, Er316, Er308 , AlMg5, AISi5 ,etc .
- Versatile functions :Hot start , arc force , anti-stick , burn back , inductance , VRD , 2T,4T, short circuit protection , thermal protection .
- Compatible with spool gun .



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40°C (%)
MIG-160-AM	220V ±15% 50/60Hz	5.5	56	30-160	0.6-1.2	1.6-3.2	40
MIG-180-AM	220V ±15% 50/60Hz	6.4	56	30-180	0.6-1.2	1.6-4.0	40
MIG-200-AM	220V ±15% 50/60Hz	7.0	56	30-200	0.6-1.2	1.6-4.0	40

MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL



VOLTAGE
OPTION 110 /220V

MIG-180PRO
MIG-200PRO

- Advanced digital signal control SYNERGIC processing.
- Multi-process :MIG , MAG ,FLUX , TIG LIFT , MMA .
- Applicable for materials :iron ,cast iron, carbon steel ,AlMg5, AlSi5 .
- Versatile functions :Hot start , arc force , anti-stick , burn back , inductance , VRD , 2T,4T, short circuit protection , thermal protection .



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40℃(%)
MIG-180PRO	220V ±15% 50/60Hz	6.1	56	30-180	0.8-1.0	1.6-3.2	40
MIG-200PRO	220V ±15% 50/60Hz	7.0	56	30-200	0.8-1.0	1.6-4.0	40

MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL



VOLTAGE
OPTION 110 /220V

MIG-140T
MIG-160T
MIG-180T
MIG-200T

- Advanced digital signal control SYNERGIC processing.
- Multi-process :MIG , MAG ,FLUX , TIG LIFT , MMA .
- Applicable for materials :iron ,cast iron, carbon steel.
- Effortless one touch setup , easy for using .
- Versatile functions :Hot start , arc force , anti-stick, short circuit protection , thermal protection .



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40℃(%)
MIG-140T	220V ±15% 50/60Hz	4.5	56	30-140	0.8-1.0	1.6-3.2	40
MIG-160T	220V ±15% 50/60Hz	5.3	56	30-160	0.8-1.0	1.6-4.0	40
MIG-180T	220V ±15% 50/60Hz	6.1	56	30-180	0.8-1.0	1.6-4.0	40
MIG-200T	220V ±15% 50/60Hz	7.0	56	30-200	0.8-1.0	1.6-4.0	40

MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL



MIG-140SNY
MIG-160SNY
MIG-180SNY
MIG-200SNY

- Advanced digital signal control SYNERGIC processing.
- Multi-process :MIG , MAG ,FLUX , TIG LIFT , MMA .
- Applicable for materials :iron ,cast iron, carbon steel , AlMg5, AlSi5 , etc .
- Effortless one touch setup , easy for using .
- Versatile functions :Hot start , arc force , anti-stick, short circuit protection , thermal protection .

VOLTAGE
OPTION110 /220V

PROCESS
OPTIONSINGLE PULSE

PARAMETERS



Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40℃(%)
MIG-140SNY	220V ± 15% 50/60Hz	4.5	56	30-140	0.8-1.0	1.6-3.2	40
MIG-160SNY	220V ± 15% 50/60Hz	5.3	56	30-160	0.8-1.0	1.6-4.0	40
MIG-180SNY	220V ± 15% 50/60Hz	6.1	56	30-180	0.8-1.0	1.6-4.0	40
MIG-200SNY	220V ± 15% 50/60Hz	7.0	56	30-200	0.8-1.0	1.6-4.0	40

MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL



MIG-164CT

- Advanced digital signal control SYNERGIC processing.
- Effortless one touch setup , easy for using .
- Multi-process :MIG , MAG ,FLUX ,CUT , MMA , TIG.
- Applicable for materials :iron , cast iron,carbon steel , stainless steel , AlMg5, AlSi5 , etc .
- Versatile functions :Hot start , arc force , anti-stick, short circuit protection , thermal protection .


VOLTAGE
OPTION110 /220V

PARAMETERS



Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Cutting current (A)	Wire diameter (mm)	Electrode diameter (mm)	Cutting thickness (mm)	Duty cycle 40℃(%)
MIG-164CT	220V ± 15% 50/60Hz	5.3	56	30-160	20-40	0.8-1.0	1.6-4.0	1-10	40

MIG(GMAW)
ANALOGY INVERTER



MIG-140E
MIG-160E
MIG-160N1
MIG-180N1
MIG-200N1

- Inverter technology.
- Multi-process MIG, MAG , FLUX, MMA.
- Versatile functions :Hot start , arc force , anti-stick , inductance , thermal protection.
- Professional welding for carbon steel , iron , cast iron.

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40 °C (%)
MIG-140E	220V±15% 50/60Hz	4.5	56	30-140	0.8-1.0	1.6_3.2	40
MIG-160E	220V±15% 50/60Hz	5.3	56	30-160	0.8-1.0	1.6-4.0	40
MIG-160N1	220V±15% 50/60Hz	5.3	56	30-160	0.8-1.0	1.6-4.0	40
MIG-180N1	220V±15% 50/60Hz	6.1	56	30-180	0.8-1.0	1.6-4.0	40
MIG-200N1	220V±15% 50/60Hz	7.0	56	30-200	0.8-1.0	1.6-5.0	40



MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL



MINI MIG-140SNY

- Advanced digital signal control SYNERGIC processing.
- Multi-process :MIG , MAG ,FLUX , TIG LIFT , MMA .
- Applicable for materials :iron ,cast iron, carbon steel .
- Effortless one touch setup , easy for using .
- Versatile functions :Hot start , arc force , anti-stick, short circuit protection , thermal protection .

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40 °C (%)
mini MIG-140SNY	220V±15% 50/60Hz	4.5	56	30-140	0.8-1.0	1.6-3.2	40



VOLTAGE OPTION 110V

MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL




FCW-120RD

- Advanced digital signal control SYNERGIC processing.
- Multi-process :FLUX , TIG LIFT , MMA .
- Applicable for materials :iron ,cast iron,mild steel .
- Effortless one touch setup , easy for using .
- Versatile functions :Hot start , arc force , anti-stick, short circuit protection , thermal protection .

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40 °C(%)
FCW-120RD	220V±15% 50/60Hz	3.7	56	30-120	0.8-1.0	1.6-2.5	40



MIG(GMAW)
SYNERGIC PROCESSING
DIGITAL SIGNAL CONTROL




FCW-120

- Advanced digital signal control SYNERGIC processing.
- Multi-process :FLUX , TIG LIFT , MMA .
- Applicable for materials :iron ,cast iron,mild steel .
- Effortless one touch setup , easy for using .
- Versatile functions :Hot start , arc force , anti-stick, short circuit protection , thermal protection .

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Current range (A)	Wire diameter (mm)	Electrode diameter (mm)	Duty cycle 40 °C(%)
FCW-120	220V±15% 50/60Hz	3.7	56	30-120	0.8-1.0	1.6-2.5	40




MMA(SMAW)
INTELLIGENT
DIGITAL SIGNAL CONTROL



iARC-140SKN
iARC-160SKN
iARC-180SKN
iARC-200SKN

- Digital signal processing .
- Multi-process : MMA and TIG lift .
- Quick ignition of arc .Stable and smooth arc .
- Suitable for rutile and basic electrode.
- Versatile functions :Hot start , arc force , anti-stick, VRD ,short circuit protection , thermal protection .


VOLTAGE
OPTION 110 /220V



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40℃(%)
iARC-140SKN	220V±15% 50/60Hz	5.0	65	20-140	1.6-4.0	40
iARC-160SKN	220V±15% 50/60Hz	5.5	65	20-160	1.6-4.0	40
iARC-180SKN	220V±15% 50/60Hz	7.0	65	20-180	1.6-5.0	40
iARC-200SKN	220V±15% 50/60Hz	8.0	65	20-200	1.6-5.0	40


MMA(SMAW)
INTELLIGENT
DIGITAL SIGNAL CONTROL



iARC-140
iARC-160
iARC-180
iARC-200

- Digital signal processing .
- Multi-process : MMA and TIG lift .
- Quick ignition of arc .Stable and smooth arc .
- Suitable for rutile and basic electrode.
- Versatile functions :Hot start , arc force , anti-stick, VRD ,seelp mode .short circuit protection , thermal protection .

VOLTAGE
OPTION 110 /220V



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40℃(%)
iARC-140	220V±15% 50/60Hz	5.0	65	20-140	1.6-4.0	40
iARC-160	220V±15% 50/60Hz	5.5	65	20-160	1.6-4.0	40
iARC-180	220V±15% 50/60Hz	7.0	65	20-180	1.6-5.0	40
iARC-200	220V±15% 50/60Hz	8.0	65	20-200	1.6-5.0	40

MMA(SMAW)
INTELLIGENT
DIGITAL SIGNAL CONTROL




iARC-140IL
iARC-160IL
iARC-180IL
iARC-200IL
iARC-225IL

6010
6013
7018

- Digital signal processing .
- Multi-process : MMA and TIG lift .
- Quick ignition of arc .Stable and smooth arc .
- Suitable for rutile and basic electrode.
- Versatile functions :Hot start , arc force , anti-stick, VRD ,short circuit protection , thermal protection .

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40 °C (%)
iARC-140 IL	220V ± 15% 50/60Hz	5.0	65	20-140	1.6-4.0	40
iARC-160 IL	220V ± 15% 50/60Hz	5.5	65	20-160	1.6-4.0	40
iARC-180 IL	220V ± 15% 50/60Hz	7.0	65	20-180	1.6-5.0	40
iARC-200 IL	220V ± 15% 50/60Hz	8.0	65	20-200	1.6-5.0	40
iARC-225 IL	220V ± 15% 50/60Hz	8.5	65	20-220	1.6-5.0	40



MMA(SMAW)
SMART INVERTER




MMA-120ZX
MMA-140ZX
MMA-140ZX-D

- Inverter technology .
- Quick ignition of arc .Stable and smooth arc .
- Versatile functions :Hot start , arc force , anti-stick, thermal protection .

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40 °C (%)
MMA-120ZX	220V ± 15% 50/60Hz	5.0	65	20-120	1.6-2.5	40
MMA-140ZX	220V ± 15% 50/60Hz	5.5	65	20-140	1.6-3.2	40
MMA-140ZX-D	220V ± 15% 50/60Hz	7.0	65	20-140	1.6-4.0	40



MMA(SMAW)
SMART INVERTER




MMA-160E
MMA-180E
MMA-200E

- Inverter technology .
- Quick ignition of arc .Stable and smooth arc .
- Versatile functions :Hot start , arc force , anti-stick, thermal protection .

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40℃(%)
MMA-160E	220V ± 15% 50/60Hz	6.0	65	20-160	1.6-4.0	40
MMA-180E	220V ± 15% 50/60Hz	7.0	65	20-180	1.6-5.0	40
MMA-200E	220V ± 15% 50/60Hz	8.0	65	20-200	1.6-5.0	40



MMA(SMAW)
SMART INVERTER



MMA-250
MMA-315
MMA-400
MMA-500


- Inverter technology .
- Multi-process : MMA and TIG lift .
- Quick ignition of arc .Stable and smooth arc .
- Robust built , strong power for heavy industry .
- Versatile functions :Hot start , arc force , VRD,anti-stick, thermal protection .

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40℃(%)
MMA-250	220V ± 15% 50/60Hz	9.2	60	20-210	1.6-5.0	40
MMA-315	380V ± 15% 50/60Hz	9.0	68	20-240	1.6-5.0	40
MMA-400	380V ± 15% 50/60Hz	15.0	72	20-350	1.6-5.0	60
MMA-500	380V ± 15% 50/60Hz	16.5	72	20-500	1.6-8.0	100




TIG(GTAW)
INTELLIGENT
DIGITAL SIGNAL CONTROL



TIG-200i


- Inverter pulse technology.
- Multi-process : TIG ,TIG pulse , MMA ,cold welding.
- High frequency arc ignition .Stable and smooth arc .
- Suitable for materials : Carbon steel , stainless steel.
- Versatile functions: Hot start , arc force , 2T. 4T , VRD , short circuit protection , thermal protection.



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40°C(%)
TIG-200i	220V ± 15% 50/60Hz	5.5	65	15-200	1.6-4.0	40


TIG(GTAW)
INTELLIGENT
DIGITAL SIGNAL CONTROL



VOLTAGE
OPTION 110 /220V

TIG-200i/PRO


- Inverter pulse technology .
- Multi-process : TIG ,TIG pulse , MMA ,cold welding.
- Save/load welding process for high efficiency .
- High frequency arc ignition .Stable and smooth arc .
- Suitable for materials : Carbon steel , stainless steel .
- Versatile functions: Hot start , arc force , 2T. 4T , VRD , short circuit protection , thermal protection .



PARAMETERS


Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40°C(%)
TIG-200i/PRO	220V ± 15% 50/60Hz	5.5	65	15-200	1.6-4.0	40

TIG(GTAW)
INTELLIGENT
DIGITAL SIGNAL CONTROL



TIG-250P
TIG-280P


- Inverter pulse technology .
- AC/DC welding current.
- Multi-process : TIG ,TIG pulse , spot welding, MMA .
- Save/load welding process for high efficiency .
- High frequency arc ignition .Stable and smooth arc .
- Suitable for materials : Carbon steel , stainless steel , aluminum .
- Versatile functions: Hot start , arc force , short circuit protection , thermal protection .



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40℃(%)
TIG-250P	220V±15% 50/60Hz	6.5	65	10-200	1.6-5.0	40
TIG-280P	220V±15% 50/60Hz	7.0	65	10-220	1.6-5.0	40

TIG(GTAW)
SMART INVERTER



TIG-160

- Inverter technology .
- Multi-process : TIG and MMA .
- High frequency arc ignition .Stable and smooth arc .
- Suitable for materials : Carbon steel , stainless steel .



PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Welding current (A)	Electrode diameter (mm)	Duty cycle 40℃(%)
TIG-160	220V±15% 50/60Hz	5.0	65	15-160	1.6-3.2	40

CUT
SMART INVERTER
AIR PLASMA CUTTING



CUT-40
CUT-60

- Inverter technology .
- High frequency arc starting .
- Integral gas regulator.
- Strong and smooth cutting ability.

PARAMETERS

Model	Power input	Input capacity (kVA)	No-load voltage (V)	Cutting range (A)	Cutting thickness (mm)	Air pressure (bar)	Duty cycle 40 °C(%)
CUT-40	220V ±15% 50/60Hz	6.6	270	20-40	1-10	2-3	40
CUT-60	220V ±15% 50/60Hz	10.4	300	20-60	1-20	4-5.5	40
CUT-60/3	380V ±15% 50/60Hz	10.4	300	20-60	1-20	4-5.5	40



CUT
SMART INVERTER
AIR PLASMA CUTTING



CUT-80
CUT-100
CUT-120

- Inverter technology.
- High frequency arc starting.
- Multi-process : CUT and MMA .
- Optional built-in air compressor .
- Strong and smooth cutting ability.

PARAMETERS

Model	Power input	No-load voltage (V)	Welding range (A)	Cutting range (A)	Cutting thickness (mm)	Air pressure (bar)	Duty cycle 40 °C(%)
CUT-80	380V ±15% 50/60Hz	310	20-200	20-80	1-25	4-5.5	40
CUT-100	380V ±15% 50/60Hz	310	20-250	20-100	1-30	4-5.5	40
CUT-120	380V ±15% 50/60Hz	310	20-250	20-120	1-35	4-5.5	40



CAR BATTERY CHARGER



CB-10
CB-15
CB-20
CB-30
CB-50
CD-30R
CD-50R

- Portable design.
- Suitable for 12/24V lead acid battery.
- Safe and fast charging / starting.

PARAMETERS

Model	Power input	Rated input power (W)	Charging current (A)	Starting current (A)	Charging voltage (V)	Charging capacity (Ah)
CB-10	220V±15% 50/60Hz	100	5/3	/	12/24	20-90
CB-15	220V±15% 50/60Hz	150	7/5	/	12/24	20-120
CB-20	220V±15% 50/60Hz	200	12/8	/	12/24	20-200
CB-30	220V±15% 50/60Hz	400	20	/	12/24	20-250
CB-50	220V±15% 50/60Hz	500	25	/	12/24	20-300
CD-30R	220V±15% 50/60Hz	400	30	80	12/24	20-400
CD-50R	220V±15% 50/60Hz	600	50	180	12/24	20-700

CAR BATTERY CHARGER



CD-300
CD-400
CD-500
CD-600
CD-800
CD-1000

- Suitable for 12/24V lead acid battery.
- Safe and fast charging / starting.
- Timer alarming.

PARAMETERS

Model	Power input	Rated input power (W)	Charging current (A)	Starting current (A)	Charging voltage (V)	Charging capacity (Ah)
CD-300	220V±15% 50/60Hz	1000	30	180	12/24	20-500
CD-400	220V±15% 50/60Hz	1400	40	240	12/24	20-700
CD-500	220V±15% 50/60Hz	1600	50	360	12/24	20-800
CD-600	220V±15% 50/60Hz	2000	60	540	12/24	20-1000
CD-800	220V±15% 50/60Hz	2200	80	650	12/24	20-1200
CD-1000	380V±15% 50/60Hz	2400	100	1000	12/24	20-1400

Blank area with horizontal dotted lines for writing.

Blank area with horizontal dotted lines for writing.

